



SELECT INDUSTRIES, INC.

P.O. Box 2450, Wichita Falls, Texas U.S. A. 76307

Ph: (940) 855-0461

(800) 234-5801

Fax: (940) 855-2734

www.selectindustries.com

SIP/Salt Pellets

In many gas wells the water that enters the well bore contains various amounts of salts (sodium chloride and other salts) dissolved in the water. Often, the fluid moves up the casing or tubing, these dissolved salts will precipitate out and reduce the opening in the pipe and in some instances totally plug the pipe.

There are various treatments for this condition such as dumping fresh water into the wells or going in with tools to clear this problem.

The SIP/SALT PELLETS helps keep the salt in solution by salt chelating action and helps prevent this build up from occurring or greatly reduces the situation.

In order to be effective the SIP/SALT PELLETS should be used regularly two or three times per week. In most wells 1-2lbs per treatment should be sufficient. Treatment amounts can be increased for large water volume situations.

If SIP/SALT PELLETS are used in conjunction with SOAP STICKS – we suggest using the SIP/SALT PELLETS on days or times when not using SOAP STICKS to get the maximum benefit from the SIP/SALT PELLETS

The pellets dissolve time will depend on temperature, salt content, and relative water motion. Pellets are 100% soluble in water.

PRODUCT PACKAGING

40 lb. plastic pail with removable lid and measuring cup

CAUTION: As with all industrial chemicals, contact with eyes or skin should be avoided (See MSDS). Wash hands thoroughly with water. Pellets should be stored in a cool dry place. Use provided measuring cup to apply pellets. Wear gloves when handling.

DISCLAIMER OF LIABILITY

The information in this bulletin is believed to be accurate, however all recommendations are made without warranty since the conditions of use are beyond Select Industries, Inc. control. Select Industries, Inc. disclaims any liability in connection with the use of the information, and does not warrant against infringement by reason of the use of any of its products in combination with any other material or in any process.